

Telescopic Crane 3203i

Technical Specifications

Material Handling Systems



Specifications	1-Manual	2-Manual	1-Hydraulic	1-Hydraulic/1-Manual
Crane Rating	10,000 ft-lb	10,000 ft-lb	10,000 ft-lb	10,000 ft-lb
Max. Horizontal Reach (from centerline of rotation)	11'	11'	11'	11'
Max. Vertical Reach	12' 1"	16' 1"	12' 1"	16' 1"
Max. Capacity	3200 lb	3200 lb	3200 lb	3200 lb
Max. Capacity at Max. Reach	954 lb	700 lb	954 lb	700 lb
Crane Weight	525 lb	600 lb	560 lb	650 lb
Crane Storage Height	27"	27"	27"	27"
Mounting Space Required	14" x 18"	14" x 18"	14" x 18"	14" x 18"
Tie-down Bolt Pattern	12" x 12" and 11.5" x 14.75"	12" x 12" and 11.5" x 14.75"	12" x 12" and 11.5" x 14.75"	12" x 12" and 11.5" x 14.75"
Min. Chassis Requirement	10,500 lb GVWR	10,500 lb GVWR	10,500 lb GVWR	10,500 lb GVWR



An Oshkosh Truck Corporation Company

