

CONDUCTOR STRINGING EQUIPMENT
4 Drum Puller/Pilot Line Winder
Model 2501



The Model 2501 is a compact and portable, hydraulic powered, 4 drum puller. It is designed to serve as a distribution conductor puller, or as a pilot rope winder to pull out the pulling rope from a single drum puller installing distribution conductors. It can be trailer or pole mounted and can be powered from a line truck, puller tensioner or other suitable hydraulic power pack.

FEATURES:

- Standard leadscrew levelwinder.
- Free wheeling drums with disc drag brakes.
- Fine control manual calipers on drag brakes.
- Individual drum clutches.
- Anti-rotation device on drive system.
- Optional trailer mounting.

PERFORMANCE (Based on 15 g.p.m. @ 2,000 psi)	EMPTY DRUM	FULL DRUM
Rated Line Pull	1,650 lbs.	875 lbs.
Maximum Line Pull @ 3,000 psi (intermittent only)	2,000 lbs.	1,000 lbs.
Line Speed	0-270 ft. per minute	0-540 ft. per minute
Average Line Speed	396 ft. per minute	

DIMENSIONS:

Length 92"
Width 52"
Height 53"
Weight (less rope).....2,100 lbs.

REEL CAPACITY:

5/16" rope8,500 ft.
3/8" rope6,000 ft.
7/16" rope4,500 ft.
1/2" rope3,500 ft.

At TSE, engineering is a process of continuous product improvement; therefore, specifications are subject to change without notice.

16-6701-062

TSE International, Inc.
5301 Shreveport-Blanchard Highway
Shreveport, Louisiana 71107

Toll Free: 800-825-2402
Telephone: 318-929-2368
FAX: 318-929-4853

www.tse-international.com