

## CONDUCTOR STRINGING EQUIPMENT *Model CT14*



### SPECIFICATIONS

Maximum Reel Torque	230,000 lbs. in.
Maximum Reel Speed	0-12 rpm (infinitely variable)
Maximum Reel Diameter	108"
Minimum Reel Diameter	48"
Maximum Reel Width	65"
Minimum Reel Width	38"
Maximum Reel Weight	16,000 lbs.
Engine Power	44 hp (not legal for US Highways)

### APPROXIMATE DIMENSIONS

Length	210"
Width	96"
Height	125"
Weight (without reel)	12,900 lbs.
GVWR	24,000 lbs.

### STANDARD FEATURES

- Infinitely variable speed control
- Infinitely variable maximum linepull control
- Spring applied hydraulic released reel brake
- Powered steering nosewheel for self propelling the unit without tow vehicle
- Hydraulic front and rear jacks
- Self loading reel arms with dual drives
- Variable displacement, closed loop hydraulic system for inching control
- 25,000 Single axle with dual wheels

### OPTIONS

- Hydraulically powered capstan
- 2,000 lb. Pilot rope winch
- Radio remote control pendants
- 500W Generator
- Auxiliary hydraulic tool circuit

At TSE, engineering is a process of continuous product improvement; therefore, specifications are subject to change without notice.

16-7640-062

**TSE International, Inc.**  
**5301 Shreveport-Blanchard Hwy**  
**Shreveport, Louisiana 71107**

**Toll Free: 800-825-2402**  
**Telephone: 318-929-2368**  
**FAX: 318-929-4853**

[www.tse-international.com](http://www.tse-international.com)