

CONDUCTOR STRINGING EQUIPMENT *Model CT6-130*



SPECIFICATIONS

Maximum reel torque	130,000 in. lb.
Maximum reel speed	0 to 12 rpm (infinitely variable)
Maximum reel diameter	84"
Minimum reel diameter	48"
Maximum reel width	60"
Minimum reel width	36"
Maximum reel weight	8,500 lbs.
Engine power (diesel)	27 hp

APPROXIMATE DIMENSIONS

Weight	7,400 lbs. (without reel)
Length	149"
Width	96"
Height	94" (without reel)

STANDARD FEATURES

- Infinitely variable speed control
- Infinitely variable maximum linepull control
- Spring applied hydraulic released reel brake
- Hydraulic front and rear jacks
- Self loading reel arms with single drive
- Variable displacement, closed loop hydraulic system for inching control
- 15,000 Single axle with dual wheels

OPTIONS

- Polemaster pilot line drive
- Auxiliary hydraulic tool circuit
- Tool storage box
- Strobe lights
- Wheel chocks and holders
- Arbor bushings



At TSE, engineering is a process of continuous product improvement; therefore, specifications are subject to change without notice.
16-7640-062

TSE International, Inc.
5301 Shreveport-Blanchard Hwy
Shreveport, Louisiana 71107

Toll Free: 800-825-2402
Telephone: 318-929-2368
FAX: 318-929-4853

www.tse-international.com