

CONDUCTOR STRINGING EQUIPMENT

Model CT6-50



STANDARD FEATURES

Infinitely variable speed control
Infinitely variable maximum linepull control
Spring applied hydraulic released reel brake
Hydraulic front and rear jacks
Self loading reel arms with single drive
Variable displacement, closed loop hydraulic system for inching control
15,000 Single axle with dual wheels

OPTIONS

Polemaster pilot line drive
Auxiliary hydraulic tool circuit
Tool storage box
Strobe lights
Wheel chocks and holders
Arbor bushings

SPECIFICATIONS

Maximum reel torque	50,000 in. lb.
Maximum reel speed	0 to 20 rpm (infinitely variable)
Maximum reel diameter	84"
Minimum reel diameter	36"
Maximum reel width	58"
Minimum reel width	27"
Maximum reel weight	8,500 lbs.
Engine power (diesel)	27 hp

APPROXIMATE DIMENSIONS

Weight	7,400 lbs. (without reel)
Length	149"
Width	96"
Height	94" (without reel)

At TSE, engineering is a process of continuous product improvement; therefore, specifications are subject to change without notice.

16-7640-062

TSE International, Inc.
5301 Shreveport-Blanchard Hwy
Shreveport, Louisiana 71107

Toll Free: 800-825-2402
Telephone: 318-929-2368
FAX: 318-929-4853

www.tse-international.com