

## CONDUCTOR STRINGING EQUIPMENT

### ***DP500 Single Drum Puller***

For Single and Bundle Transmission Conductors



#### **SPECIFICATIONS**

Maximum Continuous Linepull	30,000 lbs. @ 3.0 mph
	50,000 lbs. @ 2.1 mph
Maximum Intermittent Linepull	55,000 lbs.
Linespeed	0-3.5 mph
Engine	430 HP Diesel
Drum Capacity	32,000' of 5/8" rope
	22,000 of 3/4" rope
	16,000 of 7/8" rope

#### **STANDARD EQUIPMENT**

Self aligning spherical roller and ball bearings are used in all shaft pillow blocks.  
The frame is all steel welded construction adequately braced to ensure alignment of drive components.

#### **OPTIONAL EQUIPMENT**

Trailer mounting - fifth wheel, tandem axle including air brakes, breakaway connections with fenders and mudflaps  
High regulation lighting can also be provided  
Hydraulic operated levelwind boom  
A heavy-duty collapsible cab, complete with shatter-resistant plexiglass, protective wire screen and heater

At TSE, engineering is a process of continuous product improvement; therefore, specifications are subject to change without notice.

16-6290-062

**TSE International, Inc.**  
5301 Shreveport-Blanchard Highway  
Shreveport, Louisiana 71107

[www.tse-international.com](http://www.tse-international.com)

**Toll Free:** 800-825-2402  
**Telephone:** 318-929-2368  
**FAX:** 318-929-4853