

## CONDUCTOR STRINGING EQUIPMENT *The Pick-Up Boss System*

A safe and efficient way to install your distribution conductors

### Pick-Up Boss Puller Unit

- Performance 1,000 lbs.
- Linepull @ 120 m/min based on hydraulic supply of 15 gpm @ 2,000 psi
- Precise metering spring to neutral control valve
- Linepull limiting tension control valve
- Hydraulic pressure gauge
- Anti-rotation clutch
- Easily installed in back of 1/2 ton or larger truck
- Manual rope levelwind
- Integral self-contained hydraulic power pack
- Reliable 18 H.P. Honda gasoline engine
- Conveniently mounted control console



At TSE, engineering is a process of continuous product improvement; therefore, specifications are subject to change without notice.

16-6227-052

**TSE International, Inc.**  
5301 Shreveport-Blanchard Highway  
Shreveport, Louisiana 71107

Toll Free: 800-825-2402  
Telephone: 318-929-2368  
FAX: 318-929-4853

[www.tse-international.com](http://www.tse-international.com)

## **The Pick-Up Boss System**

A safe and efficient way to install your distribution conductors

The **Pick-up Boss** provides a completely self-contained hydraulic puller for distribution conductor stringing. It can be transported to the job site mounted on a standard pick-up, flatbed truck, or suitable trailer.



The **Pick-up Boss** utilizes all standard options from our *Poleboss System*, including brake spindles, pulling rope, and reels.



### **Payout Spindle**

- Galvanized steel frame construction
- Hot-stick adjustable disc brake
- 300 lbs. maximum braking force
- Ratchet type web binder strap
- Payout spindle weight 35 lbs.

### **Rope and Reel**

- Reel capacity: 3,000 ft. of 3/8 inch rope
- Recommended rope: 3,000 ft. of 3/8 inch rope
- Reel weight: 119 lbs.

At TSE, engineering is a process of continuous product improvement; therefore, specifications are subject to change without notice.

**TSE International, Inc.**  
5301 Shreveport-Blanchard Highway  
Shreveport, Louisiana 71107

**Toll Free: 800-825-2402**  
**Telephone: 318-929-2368**  
**FAX: 318-929-4853**

[www.tse-international.com](http://www.tse-international.com)