



CONDUCTOR STRINGING EQUIPMENT

Bullwheel Tensioner

Models T50/42 BWRC and T50/48 BWRC

MODEL T50/42 BWRC

Continuous Rated Tension	5,000 lbs.
Linespeed	0-4 mph
Bullwheel Diameter	42"
Max. Conductor Diameter	1.39"

APPROXIMATE DIMENSIONS

Length	18'-8"
Width	8'
Height	8'-3"
Weight	5,800 lbs.
GVWR	10,650 lbs.



STANDARD FEATURES

- Smooth tensioning of conductors
- Quick change reel shaft system 16" bronze disc reel brake with manual caliper
- Highway lighting
- Replaceable synthetic lining segments
- Tandem axle with leaf spring suspension

- Reel capacity 90" diameter, 53" wide and 11,000 lbs.
- Adjustable tow eye, safety chains
- One front and two rear manual jacks
- Hydraulic disc brakes, equal retarding to bullwheels
- Tail fairlead with 3 rubber lined rollers

OPTIONAL EQUIPMENT

- Increase capacity of 7,000 lbs. continuous tension
- Hydraulic reel brake caliper



MODEL T50/48 BWRC

Continuous Rated Tension	5,000 lbs.
Linespeed	0-4 mph
Bullwheel Diameter	48"
Max. Conductor Diameter	1.39"

APPROXIMATE DIMENSIONS

Length	18'-8"
Width	8'
Height	8'-3"
Weight	5,800 lbs.
GVWR	18,000 lbs.

At TSE, engineering is a process of continuous product improvement; therefore, specifications are subject to change without notice.

16-6304-062

TSE International, Inc.
 5301 Shreveport-Blanchard Highway
 Shreveport, Louisiana 71107

Toll Free: 800-825-2402
Telephone: 318-929-2368
FAX: 318-929-4853

www.tse-international.com