



**HWSC-6 Single Axle Cable Transport**  
GVWR is the empty weight & payload

GVWR .....6,000 lbs.  
 Empty Weight .....1,400 lbs.  
 Tires.....(2) 235/85R16-E  
 Wheels .....6 x 16, 8 Hole Disc  
 Brakes (Electric) .....2" x 12"  
 Maximum Reel Weight .....4,600 lbs.  
 Maximum Reel Diameter.....72"  
 Maximum Reel Width w/Out Spacers .....52"  
 Overall Width.....86"  
 Overall Length.....114"  
 Hydraulic Loading.....Double Acting  
 Frame .....Rectangular Tube  
 Towing Eye.....Adjustable Height-6 Position  
 Springs .....Multi-Leaf, Slipper Type  
 Tongue Jack .....Screw Type 7,000 lbs. w/Foot  
 Spindle Bar.....2 1/2" Dia. w/Locking Pins  
 Reel Spacers (2) .....Set Screw Locking  
 Fenders .....1/8" Steel Diamond Plate  
 Mud Flaps  
 Safety Break-Away Kit w/Jell Cell Battery  
 6-Way Electrical Plug  
 Chock Holders (Chocks Not Included)  
 4 Tail-Stop Turn Lights & License Light  
 1 Three Light Identification At Rear  
 4 Clearance Lights At Rear 2 Clearance Lights At Front  
 2 Rear Stabilizer Legs (Telescoping)  
 All Lights – Sealed Element, Grommet Mount  
 Paint .....Enamel Safety Yellow  
 Operation, Service & Parts Manual

**Options**

Surge Hydraulic Brakes	Anti-Back Lash Brake
Cargo Bed (Removeable)	Wheel Chocks
Extra Reel Width 60"	Special Paint
Special Lights	Rubber Tire Caster 8" Dia.
Warner Coupling Cable 48"	12 Volt Battery Powered Hydraulics
16" Bronze Tension Brake	Gasoline Engine Powered Hydraulics

**HWSC-80 Cable Transport  
Single Axle**

GVWR is the empty weight & payload

GVWR .....8,000 lbs.  
 Empty Weight .....1,700 lbs.  
 Tires.....(2) 12004 16.5 - F  
 Wheels (8-Hole Disc).....(2) 6.75 x 16.5  
 Axle (Oil Lubricated) .....3 1/2" Dia. (1) 8,000 lbs.  
 Springs .....Multi-Leaf, Slipper Type  
 Brakes (Electric) .....3 3/8" x 12 1/4"  
 Reel Weight (Maximum) .....6,300 lbs.  
 Reel Diameter (Maximum) .....84"  
 Reel Width w/Out Spaces (Maximum).....54"  
 Overall Width.....96"  
 Overall Length .....(approx.)144"  
 Hydraulic Loading.....(1) Hand Pump-Double Acting  
 Frame .....Rectangular Tube  
 Fenders .....1/8" Steel Diamond Plate  
 Hitch (2 5/16" Ball or Pintle Eye).....6 Position  
 Tongue Jack .....Screw Type, 7,000 lbs. Drop Leg  
 Spindle Bar w/Locking Collars.....2 1/2" O.D.  
 2 Rear Stabilizer Legs.....Pin Adjustable  
 Mud Flaps  
 Dual Safety Chains w/Safety Latch Hooks  
 Safety Break-Away Kit w/Jell Cell Battery  
 6-Way Electrical Plug  
 2 Chock Holders  
 2 Stop-Turn-Tail Lights w/Guards & License Light  
 4 Red Clearance Lights At Rear w/Reflector Lenses  
 2 Amber Clearance Lights At Front w/Reflector Lenses  
 All Lights – Sealed Element, Grommet Mount  
 Paint .....Enamel Safety Yellow  
 Operation, Service & Parts Manual

**Options**

Extra Reel Diameter	Cable Tension Brake
Extra Reel Width	Cable Retriever
10,000 lbs. Tongue Jack	Gasoline Powered Hydraulic
Tongue Jack Caster (8" dia.)	Hydraulic Power Unit Electric, 12 Volt
Special Paint	

**Built with components that match the rating for safety and everyday service.**

North Carolina  
1-336-674-7804

Idaho  
1-208-476-5662

Dealer Information: